


# ELITE Two leaves door



## Fire proof door Elite, Metal, REI 60, REI 90, REI 120 constituted by:

- Frame in galvanized steel, thickness mm. 15/10 "Z" profiled, conformed to allow coplanarity of leaf-frame, with room for insertion of intumescent strip, prearranged with steel strips for mounting on wall angles or holes for fixing on concrete.
- The connection between frame and corners occur through an unique system of joint, that first of all ensure excellent rigidity, than it avoid usual corrosion of welding.
- Nr. 2 hinges each leaf, made in sinterized steel, with sliding on two steel roller bearings, oversized for intensive usage in condition of heavy loads. Their construction allows the adjusting of the leaf position in every moment by means of special screws, normally hidden by plastic cups.
- Self closing mechanism by means of springs contained in the hinges, adjustable and invisible outside.
- Fixed rostrum placed between the hinges.
- Fireproof lock type "Patent" with cylinder and three keys.
- Fireproof lock type "flush bolt" on secondary leaf.
- Black arm closing selector (metal door excluded).
- Braccetto selettore di chiusura colore nero (escluso su porte Metal Elite).
- PVC black handle with inside steel armour, "U" shaped for accidental grips
- Thermo-expanding gasket around perimeter of the door (only for REI doors, Metal excluded).
- Superficial finishing with powder colour RAL 7035 (brushed).
- The particular construction of the door permits a perfect alignment between leaf and frame, furthermore 19 mm. thick rebated minimizes accident risks in case of contact with person. Standard handle height is mm. 950 from the floor, different height on request
- Certification range covers all ordinary type of fixing: by mounting the door in case of metal pre-frame, carton gypsum and dowels on concrete.
- Unless different agreements, door is equipped with following